


SpectralLED® RS-7-7-VIS Tunable Light Source – Light Booth



The SpectralLED® Light Booth quickly simulates virtually infinite lighting conditions enabling visual color assessment for photography, product display or lighting design applications. Both real and theoretical lighting conditions can be produced, enabling CRI experimentation, analysis and optimization.

When coupled with our line of spectroradiometers and Light Touch software, a fully non-contact digital color measurement and imaging system can be configured.

Incorporating up to 35 discrete wavelengths for synthesis of commercially available light sources, the platform is easily adaptable for automated test systems and production line integration, with integrated optical feedback and temperature control to ensure rock-solid stability and consistent results.

High Resolution and Accuracy For CRI Experimentation, Analysis and Optimization

Key Features

- All solid-state design for rapid start-up, repeatable
- Performance and long operating lifetime
- Built-in RMS spectral fitting for simulation of user
- Imported spectra
- Wavelength options from the UVA to the near infrared
- Quickly simulate any CIE illuminant or Macbeth™/XRITE™ Color Patch
- Constant current drivers and built-in optical feedback ensure accurate & flicker-free output in real time

Applications

- Image sensor / camera calibration
- Display visibility vs ambient lighting conditions
- Textile and apparel analysis
- Color assessment – consistency, stain removal and fade analysis

In addition to our exceptional technical and functional capabilities, Gamma Scientific is ISO/IEC 17025 accredited by NVLAP (NVLAP lab code 200823-0).

RS-7 Measurement Applications

- White Balance
- Quantum Efficiency
- Spatial Non-uniformity
- Pixel Defects
- Crosstalk
- Vignetting Correction
- Sensitivity
- Responsivity
- Signal to noise
- Linearity
- ISO Speed
- Saturation Exposure
- Dynamic range

Gamma Scientific is ISO/IEC 17025 accredited by NVLAP (NVLAP lab code 200823-0) and performs LM-79/LM-80 LED testing.

Optical Specifications	
Spectral Range	380 nm to 1,000 nm (custom ranges available on request)
Spectral Output	32 discrete LED channels, 3 broadband LED channels visible resolution ~ 15 nm, NIR resolution ~ 50 nm (typical channel spacing)
Spectral Bandwidth	Typical: visible 20nm FWHM, NIR 50nm FWHM
CCT Range	1,900K to 40,000K
Preset Spectra	CIE illuminants A, B, C, D50, D55, D65, D75, E, F1-F12, Macbeth™ / X-Rite™ Color Patches
Custom Preset Spectra	Configurable at time of order via API. Contact factory for details
Accuracy Specifications	
Illumination Stability	≥ 99.99% after 50 ms for radiance or after 2,000 ms for color
Illumination Accuracy	± 1% absolute, NIST traceable
Spectral Accuracy	± 1 nm centroid wavelength
Color Accuracy	CIE 1931 x, y ± 0.003
Linearity	< 0.1 % RMS of full scale
Temperature Stability	Within ± 1° C via active TEC
Long-term Drift	Output ≤ 2% Spectral ≤ 1 nm (channel dependent)
Electrical Specifications	
Electrical Resolution	16 bit DAC for channel current drivers 24 bit ADC for internal radiance monitor feedback
Dynamic Range Adjustment	4-5 decades typical (spectrum dependent)
LED Control	Pure DC constant current with floating differential sensing
General Specifications	
Software	Firmware includes full spectral calibration with spectral fitting, preset storage, real-time optical feedback, radiometric and photometric units supported
Interface Connectors	USB 2.0 type B and DB-9
Interface Protocol	Simple ASCII commands with optional binary block transfer
Supported Operating Systems	USB drivers for Windows, OSX and Linux via FTDI virtual COM port Legacy RS-232 serial port for integration (no OS required)
Input Voltage and Power	110 to 240 VAC at 50-60Hz, 600W maximum
Interior Dimensions	45 x 45 x 45 cm (preliminary)
Upgrades	
RS-7 Wavemon	Multi-channel photodiode system provides amplitude feedback and real-time wavelength measurements

Specifications are subject to change without notice.